

3 Xtrafloor® Flex Pro: total solution underlay with self-adhesive side

Specifically designed for the floating installation under Moduleo® LVT, Xtrafloor® Flex Pro offers a **comprehensive solution** to install Dryback without the need of adhesives. Xtrafloor® Flex Pro can also be used in combination with Click and loose-lay Moduleo® LVT. Its **self-adhesive side** guarantees a convenient installation: **quick, clean and simple.**

Flex Pro consists of a peelable, transparent PET-film with a high-tack self-adhesive layer, a heavy-duty polyurethane layer as well as a high-quality stabilising fleece.

Extensively tested for long-term adhesion and with high-compressive strength, this permanently elastic underlay made of mineral fibres and polyurethane binders, is **ideal for use in commercial environments.** Looking for a smart solution for your pop-up store or exhibition stand? Flex Pro guarantees **clean installation without damage to the subfloor.**

This self-adhesive underlay reduces sound impact to $\Delta Lw=13\text{dB}$ with Moduleo® Click & loose-lay and to $\Delta Lw=10\text{dB}$ with Moduleo® Dryback. And what's more: it's ready-to-use. Unlike standard adhesive installations, Flex Pro allows for the Dryback floor to be **walked on immediately** after installation. Saving you up to 40% of your time!



Time- & cost-saving: without adhesives and immediately walkable



Easy & clean (un)installation without damage to the subfloor



Suitable for castor chair use



Suitable for commercial environments, rolling loads up to 250kg



Smooths out subfloor irregularities
5mm in width, 2mm in height



Improved sound insulation
 $\Delta Lw=13\text{dB}$ with 4.5mm Moduleo® Click
 $\Delta Lw=10\text{dB}$ with 2.5mm Moduleo® Dryback



Suitable for conservatories

"How do I install a Moduleo® Dryback LVT floor that is immediately walkable, without adhesives?"

Flex Pro consists of a self-adhesive layer, a heavy-duty polyurethane layer as well as a high-quality stabilising fleece



Dimensions

Thickness: 1.8mm
Length & width: 6.5m x 1m (6.5m²/roll)
Roll weight: 16.9kg (+/- 15%)

Xtrafloor® Flex Pro

PRODUCT INFORMATION		
Composition	Permanent resilient underlay including mineral fillers and polyurethane binder	
Thickness	1.8mm	
SIZE & PACKING		
Roll format	Approx. 6.5m x 1m (6.5m ² per roll)	
Weight per sqm	2.6kg/m ²	
Weight per roll	16.9kg/roll	
TEST RESULTS		
Inflammability	EN 13501	Bfl-S1
Impact sound reduction in combination with 4.5mm Click LVT	EN ISO 10140-3	ΔLw= 13dB
Impact sound reduction in combination with 2.5mm Dryback LVT	EN ISO 10140-3	ΔLw= 10dB
Thermal resistance R	DIN 52616	0.01m ² K/W
Underfloor heating	EN 12524	Suitable, max. 27° C

