

Technical data sheet

Quick-Step Largo

Edition	01.2011	Method	Parameters	Norm requirements	Quick-Step values
General data			with v-groove all around		9,5 mm 205 mm 2050 mm 6 2,5215 m ² /pack Uniclic
Usage class	EN 13329	LPU1287,1396,1397,1398, 1399: LPU1283,1284,1285,1286,1288,1289,1505,1507:		* some test methods are not fully applicable	Class 21,22,23 & 31,32* Class 21,22,23 & 31,32
CE	EN 14041	notified body		0380-1161	
PEFC					PEFC label
Warranty		domestic use commercial use splash warranty		warranty conditions in each pack	25 year 5 year yes
Taber - wear resistance	EN 13329	LPU1287,1396,1397,1398, 1399: LPU1283,1284,1285,1286,1288,1289,1505,1507:			* with overlay class 32 ≥4000
Wear class	EN 13329	LPU1287,1396,1397,1398, 1399: LPU1283,1284,1285,1286,1288,1289,1505,1507:			* with overlay AC4 AC4
Moisture swelling	EN 13329	after 24h immersion at 20 °C		18%	10 %
General aspect of installed flooring	EN 13329	lippings opening between joints general flatness length general flatness width		<=0,15mm <=0,20mm concave<=0,50% convex<=1,00% concave<=0,15% convex<=0,20%	<=0,10 mm <=0,10 mm concave<=0,50% convex<=1,00% concave<=0,15% convex<=0,20%
Impact resistance	EN 13329			IC2	IC2
Scratch resistance	EN 438-2, 25			Charge ≥ 3.0 N	5.0 N
Staining	EN 13329	group 1,2 group 3		class 5 class 4	class 5 class 5
Light fastness	EN 13329	Blue reference		class 6	> 6
Burning cigaret	EN 438-2, 30			class 4	class 5
Displacement of furniture feet	EN 424	foot 0,1mm/32kg foot 3mm/100 kg foot 2mm/100 kg			no change no change no change
Castor chairs	EN 13329	25000 cycles		Type W(EN 12529)	no change
Dimensional variations	ISO 24339	variation length AND width			<=0,10%
Anti-static	EN 14041	charge human body at 25% RH and 23 °C			<=2,0kV
Slip resistance	EN13893				DS
Formaldehyde emission	EN 717				E1 <0,025 ppm
Thermal resistance	ISO 8302				0,061 m ² .°K/W
Underfloor heating		with appropriate underlay		Ask for specific information	OK
Impact sound reduction	ISO 712/2	3mm PE Uniclic		ΔL _w = 18 dB	ΔL _w = 18 dB
Fire classification	EN 14041				C _{fl} - s ₁

Note: For all characteristics of the surface layer, a zone of 5mm along the edge is excluded
UNILIN Flooring bvba - Ooigemstraat 3 - 8710 Wielsbeke - België
 E-mail: technical.service@quick-step.com Tel : +32 56 67 52 37 Fax : +32 56 67 52 39