

# Starfloor Click Ultimate 30

## Datasheet

| Classification                      | Norm                                                                    | Tarkett Value                                      |
|-------------------------------------|-------------------------------------------------------------------------|----------------------------------------------------|
| Product type                        | EN ISO 10582                                                            | Heterogeneous poly(vinyl chloride) floor coverings |
| Domestic classification             | EN ISO 10874                                                            | 23 Heavy                                           |
| Commercial classification           | EN ISO 10874                                                            | 31 Moderate                                        |
| Technical Characteristics           | Norm                                                                    | Tarkett Value                                      |
| Total thickness                     | EN ISO 24346                                                            | 5 mm                                               |
| Wear layer thickness                | EN ISO 24340                                                            | 0,30 mm                                            |
| Total weight                        | EN ISO 23997                                                            | 8350 g/m <sup>2</sup>                              |
| Binder content                      | EN ISO 10582                                                            | Type I                                             |
| Surface treatment                   |                                                                         | PUR Ultimate                                       |
| Bevelled edges                      |                                                                         | 4 sides micro bevels                               |
| Installation method                 |                                                                         | Click                                              |
| Performance for CE Marking          | Norm                                                                    | Tarkett Value                                      |
| Declaration of Performance #        | EN 14041                                                                | 0132-0074-DoP-2019-06                              |
| Technical Performance               | Norm                                                                    | Tarkett Value                                      |
| Dimensional stability average value | EN ISO 23999                                                            | ≤ 0,15 %                                           |
| Curl resultant to heat              | EN ISO 23999                                                            | ≤  1  mm                                           |
| Reaction to fire                    | EN 13501-1                                                              | Bfl-s1                                             |
| Residual indentation                | EN ISO 24343-1                                                          | ≤ 0,10 mm                                          |
| Furniture leg                       | EN ISO 16581                                                            | No damage                                          |
| Impact sound reduction - ΔLw        | EN ISO 717-2                                                            | 18 dB                                              |
| Reduction of in-room impact noise   | NF S31-074                                                              | Class C (≤ 85 dB)                                  |
| Thermal resistance                  | EN ISO 10456                                                            | 0,05 m <sup>2</sup> •K/W                           |
| Colour fastness to light            | EN ISO 105-B02                                                          | ≥ 6                                                |
| Chemical resistance                 | EN ISO 26987                                                            | Good resistance                                    |
| Slip resistance                     | DIN 51130                                                               | R9                                                 |
| Slip resistance                     | EN 13893                                                                | Class DS (μ ≥ 0,30)                                |
| Peeling Resistance                  | EN ISO 24345                                                            | ≥ 50N/50mm                                         |
| Static Electrical Propensity        | EN 1815                                                                 | Antistatic (≤ 2 kV)                                |
| Underfloor heating                  |                                                                         | Suitable (maximum 27°C)                            |
| Sustainability performances         | Norm                                                                    | Tarkett Value                                      |
| Total VOC Emissions                 | EN 16516                                                                | Gold (≤ 100 μg / m <sup>3</sup> )                  |
| Recyclability through ReStart®      |                                                                         | Recyclable                                         |
| Phthalate - free                    |                                                                         | Yes (except recycled content)                      |
| Dimensions and designs              |                                                                         |                                                    |
| Plank                               | Plank 1213x178mm - 8 planks=1,727 m <sup>2</sup> /box - 60 boxes/pallet |                                                    |
| Tile                                | Tile 300 x 600 mm - 9 tiles=1,62 m <sup>2</sup> /box - 60 boxes/pallet  |                                                    |
| Number of designs available         | 18                                                                      |                                                    |



The above information is subject to modification for the benefit of further improvement (22/12/2021). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.