

iD Click Ultimate 55-70 & 55-70Plus

Datasheet

	Norm	iD Click Ultimate 70	iD Click Ultimate 55	iD Click Ultimate 70Plus	iD Click Ultimate 55Plus
Classification					
Product type	EN ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings			
Domestic classification	EN ISO 10874	23 Heavy			
Commercial classification	EN ISO 10874	34 Very Heavy	33 Heavy	34 Very Heavy	33 Heavy
Industrial classification	EN ISO 10874	43 Heavy	42 General		
Technical Characteristics					
Total thickness	EN ISO 24346	6,50 mm			
Wear layer thickness	EN ISO 24340	0,70 mm	0,55 mm	0,70 mm	0,55 mm
Total weight	EN ISO 23997	11300 g/m ²	11400 g/m ²	11300 g/m ²	11400 g/m ²
Binder content	EN ISO 10582	Type I			
Surface treatment		PUR Ultimate			
Embossing in Register					Yes
Bevelled edges		4 sides micro bevels			
Installation method		Click			
Performance for CE Marking					
Declaration of Performance #	EN 14041	0197-0052-DOP-2019-08	0197-0053-DOP-2019-08	0132-0070-DoP-2018-01	
Technical Performance					
Dimensional stability	EN ISO 23999	Average measured value : ≤ 0.05 % ≤ 0,15 %			
Curl resultant to heat	EN ISO 23999	≤ 1 mm			
Reaction to fire	EN 13501-1	Bfl-s1			
Residual indentation	EN ISO 24343-1	Average measured value: 0,02 mm Required value: ≤ 0,10 mm			
Furniture leg	EN ISO 16581	No damage			
Castor chair	EN ISO 4918	No damage			
Impact sound reduction - ΔLw	EN ISO 717-2	19 dB			
Reduction of in-room impact noise	NF S31-074	Class C (≤ 85 dB)			
Thermal resistance	EN ISO 10456	0,05 m ² ·K/W			
Colour fastness to light	EN ISO 105-B02	≥ 6			
Chemical resistance	EN ISO 26987	Good resistance			
Slip resistance	DIN 51130	R9		R10 R9	
Slip resistance	EN 13893	Class DS (μ ≥ 0,30)			
Peeling Resistance	EN ISO 24345	≥ 50N/50mm			
Underfloor heating		Suitable (maximum 27°C)			
Sustainability performances					
Total VOC Emissions	EN 16516	Platinum (≤ 10 μg/m ³)		Gold (≤ 100 μg / m ³)	
Recyclability through ReStart®		Recyclable			
Recycled content		17 %			
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		12,26 kg CO ₂ e / m ²			
Total Carbon Footprint (EPD Modules A-D)		6,41 kg CO ₂ e / m ² / year			
Material Health Statement		Available			
Phthalate - free		Yes			
Dimensions and designs					
Plank		Plank 1200 x 200,5mm - 5 planks=1,2 m ² /box - 64 boxes/pallet Plank 1500 x 243mm - 3 planks=1,09 m ² /box - 69 boxes/pallet		Plank 176 x 1213 mm - 6 planks=1,281 m ² /box - 60 boxes/pallet	
Tile		480x480mm (18,9x18,9") - 5 tiles=1,15 m ² /box - 68 boxes/pallet Tile 486 x 243mm - 11 tiles=1,3 m ² /box - 56 boxes/pallet Tile 960 x 480mm - 3 tiles=1,38 m ² /box - 56 boxes/pallet			
Number of designs available		21	21	10	10



Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed.
Please contact Tarkett at the address shown for the instructions.